



WR02双圆直线导轨 Linear guides, double round rail



产品特性 Product features

- 铝合金双圆导轨，硬质氧化表面
 - 配合LIN滑动膜抵抗污物
 - 重量轻和静音
 - 安装简单，免维护
 - 标准安装宽度
- Dual guide rails made of aluminum, Hard anodized surface
 - Resistance to dirt with LIN liners
 - Weight saving and no noise
 - Simple installation, maintenance-free
 - Standard fitting width

标准规格 Standard specifications



产品编码 Part No.:

WR02-10-40-0000-NH

- 空白Blank: 带安装孔 With mounting holes
- NH: 无安装孔 No mounting holes
- 长度 Length
- 宽度 Width
- 直径 Diameter

| 产品编码 Part No. | D [mm] | di [mm] | h [mm] | h ₂ [mm] | b [mm] | a _{0.5} [mm] | a ₁ [mm] | C ₄ [mm] | C ₅ =C ₆ [mm] | | K ₁ [mm] | L max. [mm] | 重量 Weight [kg/m] |
|------------------|-----------|------------|-----------|------------------------|-----------|--------------------------|------------------------|------------------------|-------------------------------------|------|------------------------|----------------|---------------------|
| | | | | | | | | | min. | max. | | | |
| WR02-10-40-0000 | 10 | - | 5.5 | 9 | 40 | 40 | - | 120 | 20 | 79.5 | *M6 | 2500 | 1 |
| WR02-10-80-0000 | 10 | - | 5.5 | 9 | 74 | 74 | 40 | 120 | 20 | 79.5 | *M6 | 2500 | 1.5 |
| WR02-16-60-0000 | 16 | 8 | 7.5 | 14 | 58 | 54 | - | 120 | 20 | 79.5 | M8 | 2500 | 1.9 |
| WR02-20-80-0000 | 20 | 10.2 | 9.5 | 20 | 82 | 74 | 40 | 120 | 20 | 79.5 | M8 | 2500 | 3.3 |

*M6: 通孔 Plain holes

**WR02-10-40/WR02-16-60为单排安装孔 a single row of mounting holes

| 产品编码 Part No. | D [mm] | di [mm] | h [mm] | h ₂ [mm] | b [mm] | a _{0.5} [mm] | a ₁ [mm] | C ₄ [mm] | C ₅ =C ₆ [mm] | | K ₁ [mm] | L max. [mm] | 重量 Weight [kg/m] |
|--------------------|-----------|------------|-----------|------------------------|-----------|--------------------------|------------------------|------------------------|-------------------------------------|------|------------------------|----------------|---------------------|
| | | | | | | | | | min. | max. | | | |
| WR02-10-40-0000-NH | 10 | - | 5.5 | 9 | 40 | 40 | - | - | - | - | - | 2500 | 1 |
| WR02-10-80-0000-NH | 10 | - | 5.5 | 9 | 74 | 74 | - | - | - | - | - | 2500 | 1.5 |
| WR02-16-60-0000-NH | 16 | 8 | 7.5 | 14 | 58 | 54 | - | - | - | - | - | 2500 | 1.9 |
| WR02-20-80-0000-NH | 20 | 10.2 | 9.5 | 20 | 82 | 74 | - | - | - | - | - | 2500 | 3.3 |